

MoldTech

Mold Release Agent and Mold Protector Mineral Mold Oil



DESCRIPTION

MoldTech, after pouring concrete, concrete and easily separating the mold surfaces from each other and mold developed to obtain smooth surface concrete Oil.

FIELD OF APPLICATION

- In all kinds of formwork systems such as steel, plywood, plastic
- Applications to increase mold efficiency

ADVANTAGES

Provides smooth surface concrete.

- Provides easy separation of formwork from concrete and makes it easy to clean.
- It extends the life of the mold.
- Any change in concrete surface color

Why not.

- It reduces mold cost and workmanship.

USE

MoldTech, molds dry and should be clean, the mold surface should not be It should be free.

- It must be mixed before use.
- Application, brush, roller or spraying to the mold surface by one on the floor, as thin as possible and homogeneous should be done.

CONSUMPTION

In steel molds: between 80-120 ml

Plywood molds: 100 - 150 ml

In plastic molds: 120 - 200 ml

STORAGE CONDITIONS AND PACKAGING

The product must be stored above 5 0C. In case the product freezes it should be carefully mixed mechanically after thawing for restitution.

It is for sale as 25 kg plastic drum, 200 kg drums, 1000 kg plastic cubitainers and bulk.

SAFETY INFORMATION

The additive must be kept away from the skin and eyes. In case of any contact, it must be washed with water. When contacted with eyes one must immediately rinse it with water and medical support must be taken. Protective goggles / gloves / mask should be used during the usage of the admixture.

The Material Safety Data Sheet (MSDS) should be read for detailed information.

Address: Rr.Driton Islami Nr.2 Ferizaj / Kosova

Tel: + 383 49 266 333

E-posta: info@technochem.eu

Web: <https://technochem.eu>

