

# CemenTech GA

Grinding Facilitating Additives for Cement



## DESCRIPTION

CemenTech GA Series cement additives are designed for the cement industry where they facilitate grinding. Additives that facilitate grinding generally increase the yield of the mill and the flow of cement.

## FIELD OF APPLICATION

CemenTech GA Series cement additives, cement particles by reducing the electrical attraction between clumping prevents and increases the rate of cement hydration.

## ADVANTAGES

The amount of ground cement increases at the exit of the mill. Cement fineness increases by 10 - 25% and / or unit energy and the grinding cost is reduced.

## USE

Additive usage rate between 0.025% and 0.06% per ton

It varies. In the light of laboratory studies, clinker and determining the rates of other additives,

effect, effect on setting times, mortar viscosities and It is recommended to determine cement compressive strengths.

## DOSING EQUIPMENT

CemenTech GA Series is a calibrated cement additive Using the dosing system for mill efficiency suitable.

## STORAGE CONDITIONS AND PACKAGING

The product should be stored above 5 ° C. If the product is frozen, it should be mixed mechanically after thawing.

Sold in quantities of 1100kg

## SAFETY INFORMATION

The additive must be kept away from the skin and eyes. In case of any contact, it must be washed with water. When contacted with eyes one must immediately rinse it with water and medical support must be taken. Protective goggles / gloves / mask should be used during the usage of the admixture.

The Material Safety Data Sheet (MSDS) should be read for detailed information.

**Address:** Rr.Driton Islami Nr.2 Ferizaj / Kosova

**Tel:** + 383 49 266 333

**E-posta:** [info@technochem.eu](mailto:info@technochem.eu)

**Web:** <https://technochem.eu>

