

TECHNO FIX 600

Repair Mortar for Surface Repairs (Polymer reinforced) 5-30 mm



Techno Chem

DESCRIPTION

Techno Fix 600 is Cement Based Raw Concrete Repair Mortar.

USED AREA

- Repair and surface leveling of concrete defective concrete elements.
- It is used for repairing and plastering exposed concrete surfaces.
- In plaster and repair of walls and ceilings
- It is used to obtain a smooth surface before laying ceramics and tiles.

SPECIFICATIONS

- Easy to use, only mixed with water
- Provides smooth surface quality
- It provides high adhesion to concrete and plastered surfaces.
- Ease of application without cracks on wide surfaces
- High textotropic properties

SURFACE PREPARATION

It must be ensured that the surface to be repaired is strong, supportive and dust-free.

The surface must be completely cleaned from all kinds of oil waste,

Oils, rust and paraffin iron goggles that may damage adhesiveness and

Remove wood from the surface and fill the gaps up to 4 cm deep with TECHNO FIX 600. The application surface should be water-saturated, but

Free water should not remain on the surface.

Sufficient water is poured into a clean bucket.

TECHNO FIX 600 is added slowly and mixed with a 400-600 rpm mixer for 4 minutes.

Leave it until a homogeneous and lump-free mixture is obtained.

It is ready for application after mixing for almost 4 minutes and again for 30 seconds..

USE

The prepared mortar is applied to the surface with a trowel in 5-30 thickness.

The mortar is expected to draw water, sprinkle water on the mortar with a plaster brush and a trowel.

It is brought to the desired shape from steel or wood.

atmosphere, especially hot, dry or windy environments, 24-48 hours of wet wipes, rapid evaporation with water or special healing agents after application.

AIR CONDITIONS AND PACKING

It should be stored in its original package, in a cool and dry place.

up to 3 plates can be placed in short-term storage

It must overlap and the system must be implemented to make the first shipment first.

In long-term storage, pallets should not be placed on top of each other.

It is sold in 25 kg reinforced polyethylene kraft bags.

SECURITY INFORMATION

Protective measures applied to the use of common chemical products should also be considered when using this product.

Personalized information can be found about the use of this product and its transportation in the MSDS document.

For complete information on health and safety issues for this product, the SDS certificate should be consulted and this product and its box should be disposed of in accordance with local regulations. The end user of the product is responsible for this.

Adress: Rr.Driton Islami Nr.2 Ferizaj / Kosova

Tel: + 383 49 266 333

E-posta: info@technochem.eu

Web: <https://technochem.eu>

