

TECHNO ELASTO 110

Polyurethane Joint Filler Sealant Primer



DESCRIPTION

TEHNO ELASTO 110

It is an adhesive with a single, highly elastic polyurethane component, used on all internal and external surfaces, above ground surfaces, protected from air humidity and used in all horizontal and vertical joints.

USAGE ARAE

On the highway, on the road and on the bridge in the concrete field in the industrial area

In water channels and additional channel areas

For joints with a structure closer than 4 cm

In the structure and housing of the outer window, on the edges of the door frame

With PVC content, concrete, brick, wood, metal, aluminum and fugue are used for building materials

In the insulation vagina of prefabricated panels

In horizontal and vertical joints of prefabricated elements

It is used in the insulation details of all prefabricated elements in combination details.

PROPERTIES

It is a single component and ready to use product.

can be painted on

Need primer (first hand)

It fits perfectly with concrete, stone, wood and all other building materials

UV resistant

weather and water resistant

SURFACE PREPARATION

The surface should be clean, flat, stable and dry, weak parts should be removed from the surface.

Before application, fumigant should be thoroughly cleaned with a wire brush, spiral or sand, the flue spaces should be cleaned from the dust by air spraying.

USE

Be careful not to come out, only the upper parts of the joint stick with masking tape. The gun is used to place the glue on the fugue.

After TECHNO ELASTO 110 is placed in the gun, the end of the package is opened, the top of the cannula is adjusted depending on the cavity of the joint. After strengthening the mastic after 3-5, the index finger is immersed in Arab soap.

For this reason, the sealant, which is created by back and forth movements, ensures that the surface is flat. After the completion of this process, the masking strips are removed. All mastic processes should be done at + 5 ° C and above.

STORAGE AND PACKING CONDITIONS

It can be stored for 12 months in a cold and dry environment, protected from frost and unopened in its original packaging. It is offered for sale in 330 gr cartridges and 600 gr sausages.

INSURANCE INFORMATION

Protective measures applied to the use of common chemical products should also be considered when using this product. Personalized information can be found about the use of this product and its transportation in the MSDS document.

For complete information on health and safety issues for this product, the SDS certificate should be consulted and this product and its box should be disposed of in accordance with local regulations. The end user of the product is responsible for this.

Adress: Rr.Driton Islami Nr.2 Ferizaj / Kosova

Tel: + 383 49 266 333

E-posta: info@technochem.eu

Web: <https://technochem.eu>

